



# SALES FACT SHEET



## Classic<sup>®</sup> S E R I E S

### RAPL-



14 SEER Models  
Efficiencies up to 15.50 SEER  
Nominal Sizes 1 1/2 to 5 Tons  
[5.28 kW] to [17.6 kW]

#### Seven Models

Cooling Capacities  
18,200 to 59,500 BTU/HR  
[5.33 kW] to [17.44 kW]

### RANL-



13 SEER Models  
Nominal Sizes 1 1/2 to 5 Tons  
[5.28 kW] to [17.6 kW]

#### Seven Models

Cooling Capacities  
18,300 to 62,000 BTU/HR  
[5.36 kW] to [18.17 kW]

### GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Condenser Coil leaks caused by factory defects . . . . . Five (5) Years  
Compressor

JAZ . . . . . Ten (10) Years  
CAZ, DAZ, YAZ . . . . . Five (5) Years

\*Any Other Part

JAZ . . . . . Five (5) Years  
CAZ, DAZ, YAZ . . . . . One (1) Year

\*This five year limited warranty is applicable only to single-phase products installed in residential applications on or after January 1, 2001.

### Features

The Rheem *Classic<sup>®</sup> Series* High Efficiency RAPL- and RANL- Condensing Units were designed with performance in mind. These units offer comfort, energy conservation and dependability for single, multi-family and light commercial applications.

- Attractive, louvered wrap-around jacket protects the coil from yard hazards and weather extremes. Top grille is steel reinforced for extra strength. Cabinet is powder painted for all-weather protection.
- Air is discharged upward away from bushes and shrubs. The discharge pattern of the top grille provides minimum air restriction.
- Combination Grille/Motor Mount secures the motor to the underside of the discharge grille. The grille protects the motor windings and bearings from rain and snow.
- All controls are accessible by removing one service panel. Removable top grille provides access to the condenser fan motor and condenser coil.
- Single speed 8-pole fan motor designed for low speed, quiet, energy-saving operation.
- All models meet or exceed a 1000-hour salt spray test per ASTM B117 Standard Practice for Operating Salt Spray Testing Apparatus.

<u>R</u>	<u>A</u>	<u>P</u>	<u>L</u>	<u>—</u>	<u>018</u>	<u>J</u>	<u>A</u>	<u>Z</u>
RHEEM	REMOTE CONDENSING UNIT	HIGH EFFICIENCY (STANDARD) N = 13 SEER P = 14 SEER	DESIGN SERIES L=R-410A		COOLING CAPACITY 018 = 18,000 BTU/HR [5.28 kW] 024 = 24,000 BTU/HR [7.03 kW] 030 = 30,000 BTU/HR [8.79 kW] 036 = 36,000 BTU/HR [10.55 kW] 042 = 42,000 BTU/HR [12.31 kW] 048 = 48,000 BTU/HR [14.07 kW] 060 = 60,000 BTU/HR [17.58 kW]	ELECTRICAL DESIGNATION J = 208/230V-1-60 C = 208/230V-3-60 (RANL MODELS ONLY) D = 460V-3-60 (RANL MODELS ONLY) Y = 575V-3-60 (RANL 4 & 5 TON MODELS ONLY)	VARIATIONS A-SERIES = FULL-FEATURED	COOLING CONNECTION FITTING Z = SWEAT W/SCROLL

Price	Starting at: \$
-------	--------------------



(14 SEER MODELS & 13 SEER MODELS IN CERTAIN MATCHED SYSTEMS)

