



# SALES FACT SHEET



## RHPL- SERIES 16 SEER Air Handler featuring Earth-Friendly R-410A Refrigerant



### Features

- Includes an energy efficient GE® ECM® Motor, which in most applications, enhances the SEER rating of the outdoor unit. It also slowly ramps its speed up for quiet operation and enhanced customer satisfaction.
- Versatile 4-way convertible design for upflow, downflow, horizontal left and horizontal right applications.
- Nominal airflow up to 1.0" external static pressure.
- Factory-installed high efficiency indoor coil.
- Sturdy cabinet construction with 1.0 inch [25.4 mm] of foil faced insulation for excellent sound and insulating characteristics.
- Field-installed auxiliary electric heater kits provide exact heat for indoor comfort. Kits include circuit breakers which meet U.L. and cUL requirements for service disconnect.
- Dip switch settings for selectable, customized cooling airflow over a wide variety of applications.
- On-demand dehumidification terminal that adjusts airflow to help control humidity for unsurpassed comfort in cooling mode.

### GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Rheem *Prestige Series*® equipment features a 10-year limited parts warranty.\*

\*This 10-year limited parts warranty is applicable only to single-phase products installed in residential applications. For complete details of the limited warranty, including applicable terms & conditions, see your local installer or contact the manufacturer for a copy.

Price	Starting at: \$
-------	--------------------

R	H	P	L	—	HM	24	17	J	A
RHEEM	<u>CLASSIFICATION</u> H = AIR HANDLER	P = 16 SEER PREMIUM MODEL	REFRIGERANT L = R-410A	A/C OR HP MULTI- POSITION (UPFLOW/ HORIZONTAL LEFT IS THE FACTORY CONFIGURATION)	<u>CAPACITY</u> 24 = 18,000/24,000 BTU/HR [5.27/7.03 kW] 36 = 30,000/36,000 BTU/HR [6.79/10.55 kW] 48 = 42,000/48,000 BTU/HR [12.31/14.07 kW] 60 = 60,000 BTU/HR [17.58 kW]	<u>CABINET SIZE</u> 21 = 21" [533.4 mm] (1400-1600 CFM) 24 = 24.5" [609.6 mm] (1600-1800 CFM)	<u>VOLTAGE</u> J = 208/240/1/60	<u>DESIGN VARIATION</u> A = 1ST DESIGN	

