



# SALES FACT SHEET

**R-410A**  
featuring  
earth friendly refrigerant



# Classic® S E R I E S

## Features

The Rheem® *Classic Series*® RPNL- Heat Pump Outdoor units can provide year-round heating and cooling comfort for residential, multi-family and light commercial applications. They are designed to operate with Rheem indoor units with cooling and heating capacities certified under the ARI Certification program.

- Attractive, louvered wrap around jacket protects coil from weather extremes and yard hazards. Top grille is steel reinforced for extra strength. Cabinet is powder painted for all weather protection.
- Four sided outdoor coil design allows compressor operation with access panel removed.
- Air is discharged upward away from bushes and shrubs. The discharge pattern of the top grille provides minimum air restriction, resulting in quiet fan operation.
- Combination Grille/Motor Mount secures the fan motor to the underside of the discharge grille. The grille protects the motor windings and bearings from rain and snow.
- All controls are accessible by removing one service panel. Removable top grille provides access to the outdoor fan motor and outdoor coil.
- Compressor compartment offers additional protection from the elements and reduces operating noise.
- Single speed, 8-pole fan motor is designed for low speed, quieter, energy-saving operation.
- Non-cycling reversing valve and demand defrost.
- All models meet or exceed a 1000-hour salt spray test per ASTM B117 Standard Practice for Operating Salt Spray Testing Apparatus.

## RPNL- SERIES

### Seven Models

Efficiencies ranging up to 15 SEER in certain matched systems. Nominal Sizes 1 1/2 to 5 Tons [5.28 kW] to [17.58 kW]

## GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Condenser Coil leaks caused by	
factory defects .....	Five (5) Years
Compressor .....	
A-Series .....	Ten (10) Years
B-Series .....	Seven (7) Years
*Any Other Part .....	Five (5) Years

\*This five year limited warranty is applicable only to single-phase products installed in residential applications on or after January 1, 2001.

<b>R</b>	<b>P</b>	<b>N</b>	<b>L</b>	<b>—</b>	<b>024</b>	<b>J</b>	<b>A</b>	<b>Z</b>
RHEEM	REMOTE HEAT PUMP	HIGH EFFICIENCY (STANDARD)	DESIGN SERIES L = R-410A		COOLING CAPACITY	ELECTRICAL DESIGNATION	VARIATIONS	COOLING CONNECTION FITTING
					018 = 18,000 BTU/HR [5.28 kW] 024 = 24,000 BTU/HR [7.03 kW] 030 = 30,000 BTU/HR [8.79 kW] 036 = 36,000 BTU/HR [10.55 kW] 042 = 42,000 BTU/HR [12.31 kW] 048 = 48,000 BTU/HR [14.07 kW] 060 = 60,000 BTU/HR [17.58 kW]	J = 208/230V-1-60 C = 208/230V-3-60 D = 460V-3-60 Y = 575V-3-60 (4 & 5 TON ONLY)	A SERIES = FULL-FEATURED B SERIES = COMPETITIVE	Z = SWEAT W/SCROLL

Price	Starting at: \$
-------	--------------------

